

SIGALUX T8 2145/2146/2147/2148/2149/2150



Product reference	Product number	Voltage (V)	Power (W)	Power factor	Lumen (Lm)	Intensity (Cd)	Beam angle (°)	CCT (K)	Socket	Dim or not	Diameter (mm)	Length (mm)	Lifetime (h)	Switch cycles	Energy class
T8	4050497 2147	90-277	10	0.9	1000	/	160	4000	G13	not	28	600	30000	15000	A
T8	4050497 2145	90-277	10	0.9	1000	/	160	6500	G13	not	28	600	30000	15000	A
T8	4050497 2149	90-277	20	0.9	2000	/	160	4000	G13	not	28	1200	30000	15000	A
T8	4050497 2146	90-277	20	0.9	2000	/	160	6500	G13	not	28	1200	30000	15000	A
T8	4050497 2150	90-277	30	0.9	3000	/	160	4000	G13	not	28	1500	30000	15000	A
T8	4050497 2148	90-277	30	0.9	3000	/	160	6500	G13	not	28	1500	30000	15000	A

Product Features

- Compatible with existing fixtures
- Free of mercury
- ERP compliance
- warm-up time to 60% Φ : <1s
- Starting time: <0.5s
- Color consistency: < 6 step
- Color rendering index: ≥ 80
- Lumen maintenance factor at the end of the nominal life: 70%

Product Benefits

- Nature white 4000K and Cool white 6500K
- Available in G13 base

Product Applications

- Non-directional light sources
- Maybe used outdoors only in outdoor fixtures
- Working temperature: -15~+40°C